

## 1982 PLYMOUTH RELIANT

A New Measure of Efficient Service. Reliant, a bright new name in the commercial transportation business, offers particular advantages in handling, traction and maneuverability. Don't let its trim size make you think it's short on passenger room and comfort. High technology front-wheel drive is the key

to Reliant's surprisingly spacious interior. When you equip Reliant with the optional Heavy-Service Package (Code A38), you have a vehicle with everything it takes to be a money-maker. The A38 Package includes: **Heavy-duty suspension** for the extra demands in operational service.

**Power steering and power brakes** to take some of the strain out of driving, to make parking in tight spaces easier on the operator.

TorqueFlite three-speed automatic transaxle with wide-ratio design matched to engines for good economy.



Some of the items shown or described on this page and other pages are extra-cost items.

## STANDARD EQUIPMENT WITH A38 PACKAGE

NOTE: Certain models, packages and options are subject to specific restrictions, requirements or late availability. Consult your dea

	Reliant	Gran Fury
Air Cleaner—Dry type, replaceable element	S	S
—SAE-rated 78-ampere Chrysler with transistorized regulator —Heavy-duty SAE-rated 114-ampere Chrysler with transistorized	S	NA
regulator (dual-belt drive for V-8's; single belt for 6-cyl)  Ammeter and Temperature Gauge.  Antifreeze—For minus 35°F protection with higher boiling point	NA NA S	S S S S S S
Armrests — Front and rear (rear include ash receivers).  Ash Receiver — Front  Automatic Air Conditioning Compressor High-Pressure Clutch	S - S	S S
Cutoff Switch — When equipped with optional air conditioning	S	S
—2.78 to 1 —2.94 to 1 <b>Axle Size, Rear</b> —8.25" <b>Battery</b> —500-ampere Long-Life (maintenance-free): 120-minute	S NA NA	NA S S
reserve capacity	S	S
Brakes  — Heavy-duty power: dual master cylinder disc front with semi-metallic front pads; 11" x 2.5" rear drums.  — Power: dual master cylinder for separate diagonal (left front with right rear wheel, and right front with left rear wheel) braking	NA	S
systems, disc front brakes with standard semi-metallic pads; rear drums  Brakes, Power Booster—Single diaphragm Catalytic Converter. Coolant Recovery System Engine Cooling Package	S S S S	NA S S S
— Maximum capacity radiators: 22.5" width radiator with 2.2-liter 4-cyl engine, 25.0" width radiator with 2.6-liter 4-cyl engine; cooling fans: 15" diameter, four-blade fan with 2.2-liter engine, five-blade "silent fan" with optional 2.6-liter engine.  — Maximum capacity radiators: 22.0" width radiator with 6-cyl engine.	S	NA
26.0" width radiator with V-8; thermal-torque-drive cooling fans: 18" diameter with 6-cyl engine, 20" diameter with V-8	NA	S

	Reliant	Gran Fury
Engine Indicator Light—Combined oil and temperature warning light Engine Mounts—Spool type Engines	S S	NA S
— 2.2-liter, 4-cylinder.  3.7-liter (225 CID) Slant Six  Front-Wheel Drive Fuel Tank—18-gallon —13-gallon Grass Shield for Catalytic Converter—V-8 engines only. Heater with Defroster Heavy-Duty Service Package—Extra welds and reinforcements. Hood Release, Inside. Horns—Single —Dual Hubcaps, Vented Ignition—Electronic Chrysler System Interior Trim*	SASASASSSSASS	NA NA NA NA SSSS NA SSSS
—All-vinyl straight bench, heavy-duty cushion with full-foam seatback: available in blue, tan, red or green	S	NA
—Cloth-and-vinyl full bench with folding center armrest, heavy-duty cushion with full-foam seatback: available in blue, tan, red, or silver	NA	S
Mirrors —Inside, day/night, windshield -mounted —Outside left, manual, door-mounted Oil Filler Tube—Easy-Fill (V-8 engines only) Oil Filter—Full-flow, throwaway Oil Pressure Warning Light Parking Brake Warning Light Power Steering Oil Pump Cooler—V-8 engines only Rear-Wheel Drive Seat Belts—Three front, three rear (driver and right front passenger seats have combined (ap/shoulder belts)	S S NA S NA NA NA S	99999999
Shock Absorbers, Heavy-Duty —1%fe", front and rear —1¼" front, 1" rear	NA S	S